

# PERFORMANCE VALVE STEM SEALS

Engine Pro offers the solution to oil control problems in any performance valve seal situation. From seals requiring no machining to those requiring machining of the guide with a cutter, we have the answers!

- Full range of materials for all sealing needs
- Large selection of sizes



AVAILABLE  
IN BULK!



PART #	STEM DIAMETER	GUIDE DIAMETER	UNLOADED SEAL DIA.	TYPE	MATERIAL
35-8476V-16	5/16"	.476	.575	POSITIVE METAL CLAD	FLUOROVITON
35-306V-16	5/16"	.485	.625	POSITIVE	FLUOROVITON
35-805V-16	5/16"	.500	.608	POSITIVE METAL CLAD	FLUOROVITON
35-804V-16	5/16"	.502	.625	POSITIVE METAL CLAD	FLUOROVITON
35-802V-16	5/16"	.531	.680	POSITIVE METAL CLAD	FLUOROVITON
35-133P-16	11/32"			O-RING	POLYACRYLIC
35-125V-16	11/32"	.485	.630	POSITIVE METAL CLAD	FLUOROVITON
35-1611-16	11/32"	.500	.610	POSITIVE	TEFLON
35-104V-16	11/32"	.500	.625	POSITIVE	FLUOROVITON
35-104P-16	11/32"	.500	.625	POSITIVE	POLYACRYLIC
35-107V-16	11/32"	.500	.635	POSITIVE METAL CLAD	FLUOROVITON
35-1711-16	11/32"	.531	.630	POSITIVE	TEFLON
35-529V-16	11/32"	.531	.675	POSITIVE METAL CLAD	FLUOROVITON
35-408AP-16	11/32"	.531	.680	POSITIVE	POLYACRYLIC
35-371V-16	11/32"	.552	.678	POSITIVE METAL CLAD	FLUOROVITON
35-562V-16	11/32"	.562	.661	POSITIVE METAL CLAD	FLUOROVITON
35-305V-16	11/32"	.562	.700	POSITIVE	FLUOROVITON
35-304P-16	11/32"	.562	.700	POSITIVE	POLYACRYLIC
35-233V-16	11/32"	.672	.750	UMBRELLA	FLUOROVITON
35-232P-16	11/32"	.672	.750	UMBRELLA	POLYACRYLIC
35-1612-16	3/8"	.500	.600	POSITIVE	TEFLON
35-373V-16	3/8"	.500	.623	POSITIVE METAL CLAD	FLUOROVITON
35-1712-16	3/8"	.531	.630	POSITIVE	TEFLON
35-375V-16	3/8"	.531	.665	POSITIVE METAL CLAD	FLUOROVITON
35-377V-16	3/8"	.562	.675	POSITIVE METAL CLAD	FLUOROVITON

# ROTATOR ELIMINATORS FOR CHEVROLET BIG BLOCK

For use on Chevrolet Big Block applications. Eliminates O.E. rotators on the exhaust valve while providing positive location of the valve spring.


- Flat, true and dimensionally accurate
- Case hardened
- Black oxide finish



PART #	DESCRIPTION	THICKNESS	O.D.	SPRING O.D.	SPRING I.D.
03-4000-8	CHEVROLET BIG BLOCK EXHAUST ROTATOR ELIMINATOR	.300"	1.732"	1.568"	.623"

# NEW ENGINE PRO NITRO BLACK MACHINED VALVE LOCKS

Our Nitro Black valve locks are precision machined on CNC machines for accuracy and to help achieve consistent valve spring installed heights. They meet the quality standards of all Engine Pro Nitro Black products.



PART #	VALVE HEIGHT	VALVE STEM SIZE	LOCK ANGLE	LASH CAP RECESS
04-1001-32	STOCK INSTALLED HEIGHT	11/32"	7 DEGREES	NO
04-1008-32	+.050 INSTALLED HEIGHT	11/32"	7 DEGREES	NO
04-1009-32	-.050 INSTALLED HEIGHT	11/32"	7 DEGREES	NO
04-1002-32	STOCK INSTALLED HEIGHT	11/32"	10 DEGREES	YES
04-1012-32	STOCK INSTALLED HEIGHT	11/32"	10 DEGREES	NO
04-1003-32	+.050 INSTALLED HEIGHT	11/32"	10 DEGREES	NO
04-1004-32	-.050 INSTALLED HEIGHT	11/32"	10 DEGREES	NO
04-1005-32	STOCK INSTALLED HEIGHT	3/8"	7 DEGREES	NO
04-1010-32	+.050 INSTALLED HEIGHT	3/8"	7 DEGREES	NO
04-1011-32	-.050 INSTALLED HEIGHT	3/8"	7 DEGREES	NO
04-1006-32	STOCK INSTALLED HEIGHT	3/8"	10 DEGREES	YES
04-1007-32	STOCK INSTALLED HEIGHT	8MM	7 DEGREES*	NO

- High strength 1144 Stress Proof steel alloy material
- Available in 7 and 10 degree lock angles
- Black oxide finish
- Recommended for all racing applications
- Made in USA

## ALSO AVAILABLE

### STOCK REPLACEMENT STAMPED STEEL VALVE LOCKS

04-1000-32	STOCK INSTALLED HEIGHT	11/32"	7 DEGREES	NO
------------	------------------------	--------	-----------	----

- \* Bead lock for Chevrolet LS valves
- Case hardened steel
- OEM style lock is for use in stock replacement and mild performance applications

